

WHAT IS CLAIMED IS:

1. An image forming method comprising:
laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;
subjecting the plural toner layers to a primary fixing in a primary fixing step; and
subjecting the plural toner layers to a secondary fixing in a secondary fixing step to form a fixed image,
wherein the secondary fixing step is carried out under reduced pressure.
2. An image forming method according to claim 1, wherein the secondary fixing step is carried out in a non-contact manner.
3. An image forming method according to claim 1, wherein the secondary fixing step is carried out at 100 to 140°C.
4. An image forming method according to claim 1, wherein the secondary fixing step is carried by using heated rolls.
5. An image forming method according to claim 1, wherein the plural toner layers are heated under atmospheric pressure before the secondary fixing under reduced pressure in the secondary fixing step is carried out.

6. An image forming method according to claim 1, wherein the primary fixing step is carried out at a primary fixing temperature of 100 to 145°C.

7. An image forming method according to claim 4, wherein a temperature of the heated rolls in the secondary fixing step is from 120 to 170°C.

8. An image forming method according to claim 5, wherein the plural toner layers are heated in a non-contact manner in an oven.

9. An image forming method according to claim 5, wherein the plural toner layers are heated at 80 to 140°C.

10. An image forming method according to claim 1, wherein a degree of vacuum of the reduced pressure is no more than 1×10^4 Pa.

11. An image forming method according to claim 10, wherein the secondary fixing step is carried out in a non-contact manner.

12. An image forming method according to claim 10, wherein the secondary fixing step is carried out at 100 to 140°C.

13. An image forming method according to claim 10, wherein the

secondary fixing step is carried out by using heated rolls.

14. An image forming method according to claim 10, wherein the plural toner layers are heated under atmospheric pressure before the secondary fixing under reduced pressure in the secondary fixing step is carried out.

15. An image forming method according to claim 10, wherein the primary fixing step is carried out at a primary fixing temperature of 100 to 145°C.

16. An image forming method according to claim 13, wherein a temperature of the heated rolls in the secondary fixing step is from 120 to 170°C.

17. An image forming method according to claim 14, wherein the toner layers are heated in a non-contact manner in an oven.

18. An image forming method according to claim 14, wherein the toner layers are heated at 80 to 140°C.

19. An image-recorded medium formed by the steps comprising:
laminating a plurality of toner layers on a surface of a transparent substrate electrophotographically;
fixing the plural toner layers to form a fixed image; and

laminating the fixed image with a transparent laminate film,
wherein the fixed image is formed by the image forming method
according to claim 1.

20. An image-recorded medium produced by
laminating a plurality of toner layers on a surface of a transparent
substrate electrophotographically;
fixing the plural toner layers to form a fixed image; and
laminating the fixed image with a transparent laminate film,
wherein the fixed image is formed by the image forming method
according to claim 10.